

SAFETY DATA SHEET

SikaCor Thinner-8



Version
4.1

Revision Date:
27.04.2023

SDS Number:
100000014965

Date of last issue: 22.04.2021
Date of first issue: 19.11.2016

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : SikaCor Thinner-8

Manufacturer or supplier's details

Company : Sika Korea Ltd.
724, Anseongmatchum-daero
Miyang-myeon
Anseong-si
Gyeonggi-do
Korea

Telephone : +82-31-8056-7777

Emergency telephone number : +82-31-8056-7777

E-mail address : ehs@kr.sika.com

Telefax : +82-31-8056-7788

2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 2

Acute toxicity (Inhalation) : Category 4

Skin corrosion/irritation : Category 2

Serious eye damage/eye irritation : Category 2

Reproductive toxicity : Category 1B

Specific target organ toxicity - single exposure : Category 3 (Respiratory system, Central nervous system)

Specific target organ toxicity - repeated exposure : Category 2

Aspiration hazard : Category 1

GHS label elements

Hazard pictograms :



SAFETY DATA SHEET

SikaCor Thinner-8



Version
4.1

Revision Date:
27.04.2023

SDS Number:
100000014965

Date of last issue: 22.04.2021
Date of first issue: 19.11.2016

- Signal word : Danger
- Hazard statements : H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H360 May damage fertility or the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.
- Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash the contact area thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
- Response:**
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P321 Specific treatment (see supplemental first aid instructions on this label).
P331 Do NOT induce vomiting.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.

SAFETY DATA SHEET

SikaCor Thinner-8



Version
4.1

Revision Date:
27.04.2023

SDS Number:
100000014965

Date of last issue: 22.04.2021
Date of first issue: 19.11.2016

P362 + P364 Take off contaminated clothing and wash it before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents and container according to wastes control act.

Other hazards which do not result in classification

No data available

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	Common Name	CAS-No.	Concentration (% w/w)
xylene	xylene	1330-20-7	>= 45 - < 50
n-butyl acetate	n-butyl acetate	123-86-4	>= 25 - < 30
2-ethoxyethyl acetate	2-ethoxyethyl acetate	111-15-9	>= 10 - < 15
toluene	toluene	108-88-3	>= 10 - < 15
butanone	butanone	78-93-3	>= 5 - < 10

4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.

In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.

If inhaled : Move to fresh air.
Consult a physician after significant exposure.

SAFETY DATA SHEET

SikaCor Thinner-8



Version
4.1

Revision Date:
27.04.2023

SDS Number:
100000014965

Date of last issue: 22.04.2021
Date of first issue: 19.11.2016

- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : Risk of serious damage to the lungs (by aspiration).
irritant effects
toxic effects for reproduction
Aspiration may cause pulmonary oedema and pneumonitis.
Cough
Respiratory disorder
Excessive lachrymation
Headache
Dermatitis
Loss of balance
Vertigo
See Section 11 for more detailed information on health effects and symptoms.
May be fatal if swallowed and enters airways.
Causes skin irritation.
Causes serious eye irritation.
Harmful if inhaled.
May cause respiratory irritation.
May cause drowsiness or dizziness.
May damage fertility or the unborn child.
May cause damage to organs through prolonged or repeated exposure.
- Notes to physician : Treat symptomatically.

5. FIREFIGHTING MEASURES

Suitable and unsuitable extinguishing media

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : Water
- Hazardous combustion products : No hazardous combustion products are known
- Specific extinguishing methods : Use water spray to cool unopened containers.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SAFETY DATA SHEET

SikaCor Thinner-8



Version
4.1

Revision Date:
27.04.2023

SDS Number:
100000014965

Date of last issue: 22.04.2021
Date of first issue: 19.11.2016

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Remove all sources of ignition.
Deny access to unprotected persons.
- Environmental precautions : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
-

7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Use explosion-proof equipment.
Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
Take precautionary measures against electrostatic discharges.
- Advice on safe handling : Do not breathe vapours or spray mist.
Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharge.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Pregnant women or women of child-bearing age should not be exposed to this product.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Follow standard hygiene measures when handling chemical products
- Conditions for safe storage : Store in original container.
Store in cool place.
Keep in a well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Store in accordance with local regulations.
-

SAFETY DATA SHEET

SikaCor Thinner-8



Version
4.1

Revision Date:
27.04.2023

SDS Number:
100000014965

Date of last issue: 22.04.2021
Date of first issue: 19.11.2016

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis	
xylene	1330-20-7	TWA	100 ppm	KR OEL	
		STEL	150 ppm	KR OEL	
		TWA	20 ppm	ACGIH	
n-butyl acetate	123-86-4	TWA	150 ppm	KR OEL	
		STEL	200 ppm	KR OEL	
		TWA	50 ppm	ACGIH	
		STEL	150 ppm	ACGIH	
2-ethoxyethyl acetate	111-15-9	TWA	5 ppm	KR OEL	
		Further information: Presumed human reproductive toxicant, Substances designated by 'Skin' may be absorbed into the bloodstream through the skin, mucous membrane and eye and contribute to the overall effect. (Skin notation does not apply to the skin irritant)			
toluene	108-88-3	TWA	5 ppm	ACGIH	
		Further information: Suspected human reproductive toxicant			
		STEL	150 ppm	KR OEL	
		TWA	50 ppm	KR PEL	
		STEL	150 ppm	KR PEL	
		TWA	20 ppm	ACGIH	
butanone	78-93-3	TWA	200 ppm	KR OEL	
		STEL	300 ppm	KR OEL	
		TWA	200 ppm	ACGIH	
		STEL	300 ppm	ACGIH	

Other ingredients, which are listed in section 3 but not listed in this section, do not have established occupational exposure limit values.

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
xylene	1330-20-7	Methylhippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	1.5 g/g creatinine	ACGIH BEI
toluene	108-88-3	Toluene	In blood	Prior to last shift of work-week	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as	0.03 mg/l	ACGIH BEI

SAFETY DATA SHEET

SikaCor Thinner-8



Version
4.1

Revision Date:
27.04.2023

SDS Number:
100000014965

Date of last issue: 22.04.2021
Date of first issue: 19.11.2016

				possible after exposure ceases)		
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g Creatinine	ACGIH BEI
butanone	78-93-3	methyl ethyl ketone	Urine	End of shift (As soon as possible after exposure ceases)	2 mg/l	ACGIH BEI
2-ethoxyethyl acetate	111-15-9	2-Ethoxyacetic acid	Urine	End of shift at end of workweek	100 mg/g Creatinine	ACGIH BEI

Personal protective equipment. Among the following personal protective equipment, the PPEs which require safety certification need to be certified by KOSHA.

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SAFETY DATA SHEET

SikaCor Thinner-8



Version
4.1

Revision Date:
27.04.2023

SDS Number:
100000014965

Date of last issue: 22.04.2021
Date of first issue: 19.11.2016

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: transparent
Odour	: solvent-like
Odour Threshold	: No data available
pH	: Not applicable
Melting point/range / Freezing point	: No data available
Boiling point/boiling range	: No data available
Flash point	: ≤ 4 °C (39 °F) (Method: closed cup)
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available

Upper/lower flammability or explosive limits

Upper explosion limit / Upper flammability limit	: 7 %(V)
Lower explosion limit / Lower flammability limit	: 1 %(V)
Vapour pressure	: 88.9924 hPa
Solubility(ies)	
Water solubility	: No data available
Solubility in other solvents	: No data available
Density	: ca. 0.86 g/cm ³ (20 °C)
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: 415 °C
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: < 100 mPa.s (25 °C (77 °F))
Viscosity, kinematic	: < 20.5 mm ² /s (40 °C (104 °F))
Explosive properties	: No data available

SAFETY DATA SHEET

SikaCor Thinner-8



Version
4.1

Revision Date:
27.04.2023

SDS Number:
100000014965

Date of last issue: 22.04.2021
Date of first issue: 19.11.2016

Oxidizing properties : No data available

10. STABILITY AND REACTIVITY

Chemical stability and possibility of hazardous reactions : No dangerous reaction known under conditions of normal use.
The product is chemically stable.
Stable under recommended storage conditions.
Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : No data available

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : No data available

Health hazard information

Acute toxicity

Harmful if inhaled.

Components:

xylene:

Acute oral toxicity : LD50 Oral (Rat): 3,523 mg/kg

n-butyl acetate:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 23.4 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

2-ethoxyethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): 2,900 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 10,300 mg/kg

butanone:

Acute oral toxicity : LD50 Oral (Rat): 3,300 mg/kg

Acute inhalation toxicity : LC50 (Rat): 36 mg/l
Exposure time: 4 h
Test atmosphere: vapour

SAFETY DATA SHEET

SikaCor Thinner-8



Version
4.1

Revision Date:
27.04.2023

SDS Number:
100000014965

Date of last issue: 22.04.2021
Date of first issue: 19.11.2016

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Respiratory sensitisation

No data available

Skin sensitisation

No data available

Carcinogenicity

No data available

Germ cell mutagenicity

No data available

Reproductive toxicity

May damage fertility or the unborn child.

Components:

2-ethoxyethyl acetate:

According to Ministry of Employment and Labor Public Notice: Category 1B

toluene:

According to Ministry of Employment and Labor Public Notice: Category 2

STOT - single exposure

May cause respiratory irritation.

May cause drowsiness or dizziness.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Repeated dose toxicity

No data available

Aspiration toxicity

May be fatal if swallowed and enters airways.

Experience with human exposure

No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

SAFETY DATA SHEET

SikaCor Thinner-8



Version
4.1

Revision Date:
27.04.2023

SDS Number:
100000014965

Date of last issue: 22.04.2021
Date of first issue: 19.11.2016

Further information

No data available

12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

xylene:

Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): > 1.3 mg/l
Exposure time: 56 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia (water flea)): 1.17 mg/l
Exposure time: 7 d

n-butyl acetate:

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 647.7 mg/l
Exposure time: 72 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life with long lasting effects.

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SAFETY DATA SHEET

SikaCor Thinner-8



Version
4.1

Revision Date:
27.04.2023

SDS Number:
100000014965

Date of last issue: 22.04.2021
Date of first issue: 19.11.2016

Disposal precautions

Dispose of contents and container according to wastes control act.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 1263
Proper shipping name : PAINT
Class : 3
Packing group : III
Labels : 3

IATA-DGR

UN/ID No. : UN 1263
Proper shipping name : Paint
Class : 3
Packing group : III
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 366
Packing instruction (passenger aircraft) : 355

IMDG-Code

UN number : UN 1263
Proper shipping name : PAINT
Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

Refer to section 15 for specific national regulation.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

15. REGULATORY INFORMATION

National regulatory information

Regulation under the Occupational Safety and Health Act

Harmful Substances Prohibited from Manufacturing

Not applicable

SAFETY DATA SHEET

SikaCor Thinner-8



Version
4.1

Revision Date:
27.04.2023

SDS Number:
100000014965

Date of last issue: 22.04.2021
Date of first issue: 19.11.2016

Harmful Substances Required Permission for Manufacture

Not applicable

Harmful Agents to be kept below Occupational Exposure Limits

Chemical name	CAS-No.
Xylene (all isomers)	1330-20-7
n-Butyl acetate	123-86-4
2-Ethoxyethyl acetate	111-15-9
Toluene	108-88-3
Methyl ethyl ketone	78-93-3

Harmful Agents Required to be kept below Permission Levels

Chemical name	CAS-No.
Toluene	108-88-3

Hazardous substances requiring management

Chemical name	CAS-No.	Threshold limits (%)
Xylene	1330-20-7	≥ 1 %
n-Butyl acetate	123-86-4	≥ 1 %
2-Ethoxyethyl acetate	111-15-9	≥ 1 %
Toluene	108-88-3	≥ 1 %
Methyl ethyl ketone	78-93-3	≥ 1 %

Special Management Materials

Chemical name	CAS-No.	Threshold limits (%)
2-Ethoxyethyl acetate	111-15-9	≥ 0.3 %

Controlled Substances Subject to Environment Monitoring

Chemical name	CAS-No.	Threshold limits (%)
Xylene	1330-20-7	≥ 1 %
n-Butyl acetate	123-86-4	≥ 1 %
2-Ethoxyethyl acetate	111-15-9	≥ 1 %
Toluene	108-88-3	≥ 1 %
Methyl ethyl ketone	78-93-3	≥ 1 %

Controlled Substances Subject to Health Examination

Chemical name	CAS-No.	Threshold limits (%)
Xylene	1330-20-7	≥ 1 %
2-Ethoxyethyl acetate	111-15-9	≥ 1 %
Toluene	108-88-3	≥ 1 %
Methyl ethyl ketone	78-93-3	≥ 1 %

Regulation under the Chemicals Control Act

Toxic Chemicals

Not applicable

Restricted Chemicals

Not applicable

Prohibited Chemicals

Not applicable

SAFETY DATA SHEET

SikaCor Thinner-8



Version
4.1

Revision Date:
27.04.2023

SDS Number:
100000014965

Date of last issue: 22.04.2021
Date of first issue: 19.11.2016

Toxic Release Inventory

Chemical name	CAS-No.	Group	Threshold limits (%)
Xylene (o-,m-,p- isomer mixture)	1330-20-7	Group II	>= 1 %
2-Ethoxyethyl acetate	111-15-9	Group II	>= 0.1 %
Toluene	108-88-3	Group II	>= 1 %
Methyl ethyl ketone	78-93-3	Group II	>= 1 %

Accident Precaution Chemicals

Not applicable

Dangerous Substances Safety Management Act

Classification : Group 4, Flammable liquids, Type 1 petroleums, Water insoluble liquid

Hazard rank : Hazardous rank II

Designated Quantity : 200 litre

Safety Warning : Keep away from fire

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors : Not applicable

라. Wastes Control Act

Industrial waste

Follow article 13 of the act to dispose the product waste

마. Other requirements in domestic and other countries

The components of this product are reported in the following inventories:

ENCS : On the inventory, or in compliance with the inventory

ISHL : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

16. OTHER INFORMATION

Issuing date : 19.11.2016

Revision number and date

Number of Revision : 4.1

Revision Date : 27.04.2023

Date format : yyyy/mm/dd

SAFETY DATA SHEET

SikaCor Thinner-8




Version
4.1

Revision Date:
27.04.2023

SDS Number:
100000014965

Date of last issue: 22.04.2021
Date of first issue: 19.11.2016

NFPA:



Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	: ACGIH - Biological Exposure Indices (BEI)
KR OEL	: Harmful Agents to be kept below Occupational Exposure Limits
KR PEL	: Harmful Agents Required to be kept below Permission Levels
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
KR OEL / TWA	: Time Weighted Average
KR OEL / STEL	: Short Term Exposure Limit
KR PEL / TWA	: TWA
KR PEL / STEL	: STEL
ADR	: European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	: Chemical Abstracts Service
DNEL	: Derived no-effect level
EC50	: Half maximal effective concentration
GHS	: Globally Harmonized System
IATA	: International Air Transport Association
IMDG	: International Maritime Code for Dangerous Goods
LD50	: Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	: Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	: International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	: Occupational Exposure Limit
PBT	: Persistent, bioaccumulative and toxic
PNEC	: Predicted no effect concentration
REACH	: Regulation (EC) No 1907/2006 of the European Parliament

SAFETY DATA SHEET

SikaCor Thinner-8



Version
4.1

Revision Date:
27.04.2023

SDS Number:
100000014965

Date of last issue: 22.04.2021
Date of first issue: 19.11.2016

SVHC
vPvB

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
: Substances of Very High Concern
: Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

KR / EN