

SAFETY DATA SHEET

SikaPower®-498/3



Version
2.0

Revision Date:
08.04.2025

SDS Number (Internal):
100000003524

Date of last issue: 04.02.2022
Date of first issue: 04.02.2022

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : SikaPower®-498/3

Recommended use of the chemical and restrictions on use

Product use : Adhesive, For professional users only.

Manufacturer or supplier's details

Company : Sika Korea Ltd.
724, Anseongmatchum-daero
Miyang-myeon
Anseong-si
Gyeonggi-do
Korea

Telephone : +82-31-8056-7777

Emergency telephone number : +82-31-8056-7777

E-mail address : ehs@kr.sika.com

Telefax : +82-31-8056-7788

2. HAZARDS IDENTIFICATION

GHS Classification

Skin corrosion/irritation : Category 2

Serious eye damage/eye irritation : Category 2

Skin sensitisation : Category 1

Long-term (chronic) aquatic hazard : Category 2

GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.

SAFETY DATA SHEET

SikaPower®-498/3



Version
2.0

Revision Date:
08.04.2025

SDS Number (Internal):
100000003524

Date of last issue: 04.02.2022
Date of first issue: 04.02.2022

Precautionary statements

- Prevention:**
P261 Avoid breathing mist or vapours.
P264 Wash skin thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.
P273 Avoid release to the environment.
P280 Wear protective gloves/ eye protection/ face protection.
- Response:**
P302 + P352 IF ON SKIN: Wash with plenty of water.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P321 Specific treatment (see supplemental first aid instructions on this label).
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P391 Collect spillage.
- Disposal:**
P501 Dispose of contents/ container according to waste-related laws

Other hazards which do not result in classification

No data available

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	Common Name	CAS-No.	Concentration (% w/w)
bis-[4-(2,3-epoxipropoxy)phenyl]propane	bis-[4-(2,3-epoxypropoxy)phenyl]propane	1675-54-3	>= 30 - < 35
reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number average molecular weight 700 - 1100)	reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number average molecular weight	25068-38-6	>= 10 - < 15

SAFETY DATA SHEET

SikaPower®-498/3



Version
2.0

Revision Date:
08.04.2025

SDS Number (Internal):
100000003524

Date of last issue: 04.02.2022
Date of first issue: 04.02.2022

	700 - 1100)		
Aliphatic polyurethane prepolymer polyoxy-alkylene based, blocked	Aliphatic polyurethane prepolymer polyoxy-alkylene based, blocked	1256351-42-4	$\geq 5 - < 10$
Aliphatic polyurethane prepolymer polyoxy-alkylene based, blocked	Aliphatic polyurethane prepolymer polyoxy-alkylene based, blocked	1617507-45-5	$\geq 5 - < 10$
amorphous silicon dioxide	amorphous silicon dioxide	67762-90-7	$\geq 5 - < 10$
calcium oxide	calcium oxide	1305-78-8	$\geq 3 - < 5$
p-tert-butylphenyl 1-(2,3-epoxy)propyl ether	p-tert-butylphenyl 1-(2,3-epoxy)propyl ether	3101-60-8	$\geq 1 - < 5$
Cashew, nutshell liq.	Cashew, nutshell liq.	8007-24-7	$\geq 0.25 - < 1$
mequinol	mequinol	150-76-5	$0 - < 1$

4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- In case of eye contact : Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Obtain medical attention.
- Most important symptoms and effects, both acute and : Causes skin irritation.
May cause an allergic skin reaction.

SAFETY DATA SHEET

SikaPower®-498/3



Version 2.0	Revision Date: 08.04.2025	SDS Number (Internal): 100000003524	Date of last issue: 04.02.2022 Date of first issue: 04.02.2022
----------------	------------------------------	--	---

delayed Causes serious eye irritation.
sensitising effects
Allergic reactions
See Section 11 for more detailed information on health effects
and symptoms.

Notes to physician : Treat symptomatically.

5. FIREFIGHTING MEASURES

Suitable and unsuitable extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

Specific extinguishing methods : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Deny access to unprotected persons.

Environmental precautions : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

SAFETY DATA SHEET

SikaPower®-498/3



Version
2.0

Revision Date:
08.04.2025

SDS Number (Internal):
100000003524

Date of last issue: 04.02.2022
Date of first issue: 04.02.2022

section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Follow standard hygiene measures when handling chemical products

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Store in accordance with local regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
calcium oxide	1305-78-8	TWA	2 mg/m ³	KR OEL
		TWA	2 mg/m ³	ACGIH
mequinol	150-76-5	TWA	5 mg/m ³	KR OEL
		TWA	5 mg/m ³	ACGIH

Other ingredients, which are listed in section 3 but not listed in this section, do not have established occupational exposure limit values.

Personal protective equipment. Among the following personal protective equipment, the PPEs which require safety certification need to be certified by KOSHA.

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

SAFETY DATA SHEET

SikaPower®-498/3



Version
2.0

Revision Date:
08.04.2025

SDS Number (Internal):
100000003524

Date of last issue: 04.02.2022
Date of first issue: 04.02.2022

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Colour : grey

Odour : odourless

Odour Threshold : No data available

pH : Not applicable substance/mixture is non-soluble (in water)

Melting point/ range / Freezing point : No data available

Boiling point/boiling range : No data available

Flash point : > 150 °C (> 302 °F)
(Method: closed cup)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper/lower flammability or explosive limits

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapour pressure : 0.01 hPa

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Density : ca. 1.28 g/cm³ (20 °C)

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

SAFETY DATA SHEET

SikaPower®-498/3



Version 2.0	Revision Date: 08.04.2025	SDS Number (Internal): 100000003524	Date of last issue: 04.02.2022 Date of first issue: 04.02.2022
----------------	------------------------------	--	---

Viscosity
Viscosity, dynamic : No data available
Viscosity, kinematic : > 20.5 mm²/s (40 °C (104 °F))
Explosive properties : No data available
Oxidizing properties : No data available

10. STABILITY AND REACTIVITY

Chemical stability and possibility of hazardous reactions : Reactivity:
No dangerous reaction known under conditions of normal use.
Chemical stability:
The product is chemically stable.
Possibility of hazardous reactions:
Stable under recommended storage conditions.

Conditions to avoid : No data available

Incompatible materials : No data available

Hazardous decomposition products : No hazardous decomposition products are known.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : No data available

Health hazard information

Acute toxicity

No data available

Components:

bis-[4-(2,3-epoxipropoxy)phenyl]propane:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg
Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

amorphous silicon dioxide:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

p-tert-butylphenyl 1-(2,3-epoxy)propyl ether:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg
Acute inhalation toxicity : LC50 (Rat): 3,466 mg/l

SAFETY DATA SHEET

SikaPower®-498/3



Version
2.0

Revision Date:
08.04.2025

SDS Number (Internal):
100000003524

Date of last issue: 04.02.2022
Date of first issue: 04.02.2022

Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rabbit): 6,000 mg/kg

Cashew, nutshell liq.:

Acute oral toxicity : LD50 Oral (Rat): 500 mg/kg

Acute dermal toxicity : LD50 Dermal (Rat): 2,000 mg/kg

mequinol:

Acute oral toxicity : LD50 Oral (Rat): 1,630 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Respiratory sensitisation

No data available

Skin sensitisation

May cause an allergic skin reaction.

Carcinogenicity

No data available

Components:

bis-[4-(2,3-epoxipropoxy)phenyl]propane:

No data available

reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number average molecular weight 700 - 1100):

No data available

Aliphatic polyurethane prepolymer polyoxyalkylene based, blocked:

No data available

Aliphatic polyurethane prepolymer polyoxyalkylene based, blocked:

No data available

amorphous silicon dioxide:

No data available

SAFETY DATA SHEET

SikaPower®-498/3



Version
2.0

Revision Date:
08.04.2025

SDS Number (Internal):
100000003524

Date of last issue: 04.02.2022
Date of first issue: 04.02.2022

calcium oxide:

No data available

p-tert-butylphenyl 1-(2,3-epoxy)propyl ether:

No data available

Cashew, nutshell liq.:

No data available

mequinol:

No data available

Germ cell mutagenicity

No data available

Components:

bis-[4-(2,3-epoxipropoxy)phenyl]propane:

No data available

reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number average molecular weight 700 - 1100):

No data available

Aliphatic polyurethane prepolymer polyoxyalkylene based, blocked:

No data available

Aliphatic polyurethane prepolymer polyoxyalkylene based, blocked:

No data available

amorphous silicon dioxide:

No data available

calcium oxide:

No data available

p-tert-butylphenyl 1-(2,3-epoxy)propyl ether:

No data available

Cashew, nutshell liq.:

No data available

mequinol:

No data available

SAFETY DATA SHEET

SikaPower®-498/3



Version
2.0

Revision Date:
08.04.2025

SDS Number (Internal):
100000003524

Date of last issue: 04.02.2022
Date of first issue: 04.02.2022

Reproductive toxicity

No data available

Components:

bis-[4-(2,3-epoxipropoxy)phenyl]propane:

No data available

reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number average molecular weight 700 - 1100):

No data available

Aliphatic polyurethane prepolymer polyoxyalkylene based, blocked:

No data available

Aliphatic polyurethane prepolymer polyoxyalkylene based, blocked:

No data available

amorphous silicon dioxide:

No data available

calcium oxide:

No data available

p-tert-butylphenyl 1-(2,3-epoxy)propyl ether:

No data available

Cashew, nutshell liq.:

No data available

mequinol:

Suspected of damaging fertility or the unborn child.

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Repeated dose toxicity

No data available

Aspiration toxicity

No data available

SAFETY DATA SHEET

SikaPower®-498/3



Version
2.0

Revision Date:
08.04.2025

SDS Number (Internal):
100000003524

Date of last issue: 04.02.2022
Date of first issue: 04.02.2022

Experience with human exposure

No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information

Product:

Remarks : Toxicology data for the components
Information given is based on data on the components and
the toxicology of similar products.
Based on available data, the classification criteria are not met.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

bis-[4-(2,3-epoxipropoxy)phenyl]propane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1.8 mg/l
aquatic invertebrates Exposure time: 48 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor- : An environmental hazard cannot be excluded in the event of
mation unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Send to a licensed waste management company.

SAFETY DATA SHEET

SikaPower®-498/3



Version	Revision Date:	SDS Number (Internal):	Date of last issue: 04.02.2022
2.0	08.04.2025	100000003524	Date of first issue: 04.02.2022

The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.

Do not re-use empty containers.

Disposal precautions

Dispose of contents and container according to wastes control act.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3077
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
(epoxy resin, p-tert-butylphenyl 1-(2,3-epoxy)propyl ether)

Class : 9
Packing group : III
Labels : 9
Environmentally hazardous : yes

IATA-DGR

UN/ID No. : UN 3077
Proper shipping name : Environmentally hazardous substance, solid, n.o.s., Environmentally hazardous substance, solid, n.o.s.
(epoxy resin, p-tert-butylphenyl 1-(2,3-epoxy)propyl ether)

Class : 9
Packing group : III
Labels : Miscellaneous
Packing instruction (cargo aircraft) : 956
Packing instruction (passenger aircraft) : 956
Environmentally hazardous : yes

IMDG-Code

UN number : UN 3077
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
(epoxy resin, p-tert-butylphenyl 1-(2,3-epoxy)propyl ether)

Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes

SAFETY DATA SHEET

SikaPower®-498/3



Version
2.0

Revision Date:
08.04.2025

SDS Number (Internal):
100000003524

Date of last issue: 04.02.2022
Date of first issue: 04.02.2022

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

Refer to section 15 for specific national regulation.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

15. REGULATORY INFORMATION

National regulatory information

Regulation under the Occupational Safety and Health Act

Harmful Substances Prohibited from Manufacturing

Not applicable

Harmful Substances Required Permission for Manufacture

Not applicable

Harmful Agents to be kept below Occupational Exposure Limits

Chemical name	CAS-No.
Calcium oxide	1305-78-8
4-Methoxyphenol	150-76-5

Harmful Agents Required to be kept below Permission Levels

Not applicable

Hazardous substances requiring management

Chemical name	CAS-No.	Threshold limits (%)
2,3-Epoxy-1-propanol	1675-54-3	>= 1 %

Special Management Materials

Chemical name	CAS-No.	Threshold limits (%)
2,3-Epoxy-1-propanol	1675-54-3	>= 0.1 %

Controlled Substances Subject to Environment Monitoring

Chemical name	CAS-No.	Threshold limits (%)
2,3-Epoxy-1-propanol	1675-54-3	>= 1 %

Controlled Substances Subject to Health Examination

Chemical name	CAS-No.	Threshold limits (%)
2,3-Epoxy-1-propanol	1675-54-3	>= 1 %

Hazardous Substances Subject to Process Safety Management (PSM) Reporting Obligation

Not applicable

K-OSHA Hazardous Substances (Occupational Safety and Health Regulations, Table 1)

Category
Corrosive substances

SAFETY DATA SHEET

SikaPower®-498/3



Version
2.0

Revision Date:
08.04.2025

SDS Number (Internal):
100000003524

Date of last issue: 04.02.2022
Date of first issue: 04.02.2022

|| Acute toxic substances (inhalation)

K-OSHA Hazardous Substances (Occupational Safety and Health Regulations, Table 9)

Category	Manufacturing or handling quantity
Corrosive substances	300 kilogram
Acute toxic substances (inhalation)	100 kilogram

Regulation under the Chemicals Control Act

Toxic Chemicals

Not applicable

Restricted Chemicals

Not applicable

Prohibited Chemicals

Not applicable

Toxic Release Inventory

Chemical name	CAS-No.	Group	Threshold limits (%)
4,4'-(1-Methylethylidene)bisphenol polymer with (chloromethyl)oxirane	25068-38-6	Group II	>= 1 %
4,4'-(1-Methylethylidene)bisphenol polymer with (chloromethyl)oxirane	25068-38-6	Group II	>= 1 %

Accident Precaution Chemicals

Not applicable

Dangerous Substances Safety Management Act

Classification : Group 4, Flammable liquids, Type 3 petroleum, Water insoluble liquid

Hazard rank : Hazardous rank III

Designated Quantity : 2000 litre

Safety Warning : Keep away from fire

International Chemical Weapons Convention (CWC) : Not applicable
Schedules of Toxic Chemicals and Precursors

라. Wastes Control Act

Industrial general wastes
Follow article 13 of the act to dispose the product waste

마. Other requirements in domestic and other countries

The components of this product are reported in the following inventories:

ENCS : Not in compliance with the inventory

ISHL : Not in compliance with the inventory

SAFETY DATA SHEET

SikaPower®-498/3



Version
2.0

Revision Date:
08.04.2025

SDS Number (Internal):
100000003524

Date of last issue: 04.02.2022
Date of first issue: 04.02.2022

KECI : Not in compliance with the inventory


16. OTHER INFORMATION

Issuing date : 04.02.2022

Revision number and date

Number of Revision : 2.0
Revision Date : 08.04.2025
Date format : yyyy/mm/dd

NFPA:



Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
KR OEL : Harmful Agents to be kept below Occupational Exposure Limits

ACGIH / TWA : 8-hour, time-weighted average
KR OEL / TWA : Time Weighted Average
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level
EC50 : Half maximal effective concentration
GHS : Globally Harmonized System
IATA : International Air Transport Association
IMDG : International Maritime Code for Dangerous Goods
LD50 : Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)

LC50 : Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)

SAFETY DATA SHEET

SikaPower®-498/3



Version 2.0	Revision Date: 08.04.2025	SDS Number (Internal): 100000003524	Date of last issue: 04.02.2022 Date of first issue: 04.02.2022
----------------	------------------------------	--	---

MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

KR / EN