

PRODUCT DATA SHEET

SikaRoof® Decor Profile FPO AP

FPO DECOR PROFILE

DESCRIPTION

SikaRoof® Decor Profile FPO AP is an FPO extruded profile made which is welded to Sarnafil® T (FPO) sheet waterproofing membranes to replicate standing seam metal roofing systems.

USES

SikaRoof® Decor Profile FPO AP may only be used by experienced professionals.

- Creating an appearance of a standing seam metal roof

FEATURES

- Applicable for exposed roofing
- Easily applied
- Resistant to UV exposure
- Suitable for any roof slope
- Hot air weldable
- Available in various colours
- Recyclable



PRODUCT INFORMATION

Composition	Flexible polyolefins based on polypropylene (PP)	
Packaging	1 pieces	
Appearance and colour	Surface	smooth
	Colour	window grey (nearest RAL 7040)
		Light grey (nearest RAL 7035)
		white (nearest RAL 9016)
Shelf life	5 years from date of production.	
Storage conditions	The products must be stored in original, unopened and undamaged sealed packaging in dry conditions at temperatures between +5 °C and +30 °C. Always refer to packaging.	
Length	2000 mm (+10 mm / -10 mm)	

Width	35 mm (+1mm / -1mm)
Mass per area	210 g/m
Height	25 mm (+1mm / -1mm)

TECHNICAL INFORMATION

Reaction to fire	Class E	(EN 13501-1)
------------------	---------	--------------

APPLICATION INFORMATION

Ambient air temperature	-20 °C min. / +60 °C max.
-------------------------	---------------------------

Substrate temperature	-30 °C min. / +60 °C max.
-----------------------	---------------------------

SYSTEM INFORMATION

System structure	The following products must be considered for use depending on roof design: ▪ Sarnafil® TS 77-types ▪ Sarnafil® TG 76-types
------------------	--

BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

IMPORTANT CONSIDERATIONS

Installation work must only be carried out by Sika® trained and approved contractors, experienced in this type of application.

- The use of some ancillary products such as adhesives, cleaners and solvents is limited to temperatures above +5 °C. Observe temperature limitations in the appropriate Product Data Sheets.
- Special measures may be compulsory for installation below +5 °C ambient temperature due to safety requirements in accordance with national regulations.

ECOLOGY, HEALTH AND SAFETY

Fresh air ventilation must be ensured, when working (welding) in closed rooms.

REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w)

APPLICATION INSTRUCTIONS

APPLICATION

Installation procedure

Ensure the SikaRoof® Decor Profile FPO AP is tacked into position at the desired centres and hot air weld into place to the roof membrane. Join two or more SikaRoof® Decor Profile FPO APs together, using the connector plugs supplied. Finish the end of the profile with a piece of hot air welded membrane if required.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

한국지식(S)

02094 222 222 1350 16

Tel : +82 2 6912 1500

Fax : +82 2 6912 1555

web: <http://kor.sika.com>

Sika Korea Ltd.

419 Nonhyeon-ro, PMK Building 3rd floor

Gangnam-ku, Seoul, Korea

Tel : +82 2 6912 1500

Fax: +82 2 6912 1555

web: <http://kor.sika.com>



Product Data Sheet
SikaRoof® Decor Profile FPO AP
January 2026, Version 01.01
020945032150247713

SikaRoofDecorProfileFPOAP-en-KR-(01-2026)-1-1.pdf