

PRODUCT DATA SHEET

Sikafloor® RA Lining

2K ANTI-ACID EPOXY RA-LINING

DESCRIPTION

Sikafloor® RA Lining is a two-liquid epoxy lining paint of epoxy resin and degeneration amine type, which is resistant to strong acid or strong alkali and is used to prevent corrosion of exposed concrete under extreme environmental conditions.

USES

Sikafloor® RA Lining may only be used by experienced professionals.
Acid-resistant paint used for concrete floors and chemical corrosion-resistant conditions that require resistance.

CHARACTERISTICS / ADVANTAGES

- Excellent durability for acid or alkaline.
- Excellent resistance to various kinds of medicines.

PRODUCT INFORMATION

Packaging	Sikafloor RA-Lining PT-A	12.9kg
	Sikafloor RA-Lining PT-B	5.1kg
Shelf life	12 months	
Storage conditions	Keep in shady, well ventilated places and cover the tent to avoid direct sunlight when outdoors.	

BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the

declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer

to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Korea Ltd.

135 gil 16, Nonhyun-ro
Gangnam-ku, Seoul, Korea
Tel : +82 2 6912 1500
Fax: +82 2 6912 1555
web: <http://kor.sika.com>



Product Data Sheet
Sikafloor® RA Lining
March 2019, Version 01.01
020811020020000150

SikafloorRALining-en-KR-(03-2019)-1-1.pdf