

# SAFETY DATA SHEET

## Sika® Aktivator-100



Version  
4.1

Revision Date:  
19.09.2025

SDS Number (Internal):  
000000033123

Date of last issue: 10.08.2023  
Date of first issue: 22.12.2015

---

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sika® Aktivator-100

#### Recommended use of the chemical and restrictions on use

Product use : Pretreatment agent

#### Manufacturer or supplier's details

Company : Sika Korea Ltd.  
724, Anseongmatchum-daero  
Miyang-myeon  
Anseong-si  
Gyeonggi-do  
Korea

Telephone : +82-31-8056-7777

Emergency telephone number : +82-31-8056-7777

E-mail address : ehs@kr.sika.com

Telefax : +82-31-8056-7788

---

### 2. HAZARDS IDENTIFICATION

#### GHS Classification

Flammable liquids : Category 2

Skin corrosion/irritation : Category 2

Serious eye damage/eye irritation : Category 2

Skin sensitisation : Category 1

Carcinogenicity : Category 1A

Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

Aspiration hazard : Category 1

Long-term (chronic) aquatic hazard : Category 2

#### GHS label elements

# SAFETY DATA SHEET

## Sika® Aktivator-100



Version  
4.1

Revision Date:  
19.09.2025

SDS Number (Internal):  
000000033123

Date of last issue: 10.08.2023  
Date of first issue: 22.12.2015

Hazard pictograms

:



Signal word

:

Danger

Hazard statements

:

H225 Highly flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H350 May cause cancer.  
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

:

### Prevention:

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P240 Ground and bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.  
P242 Use non-sparking tools.  
P243 Take action to prevent static discharges.  
P261 Avoid breathing mist or vapours.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

### Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
P321 Specific treatment (see supplemental first aid instructions on this label).  
P331 Do NOT induce vomiting.

# SAFETY DATA SHEET

## Sika® Aktivator-100



Version  
4.1

Revision Date:  
19.09.2025

SDS Number (Internal):  
000000033123

Date of last issue: 10.08.2023  
Date of first issue: 22.12.2015

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.  
P391 Collect spillage.

### Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

### Disposal:

P501 Dispose of contents/ container according to waste-related laws

### Other hazards which do not result in classification

No data available

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Components

Chemical name	Common Name	CAS-No.	Concentration (% w/w)
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	64742-49-0	>= 80 - < 85
ethanol	ethanol	64-17-5	>= 5 - < 10
N-(3-(trimethoxysilyl)propyl)ethylenediamine	N-(3-(trimethoxysilyl)propyl)ethylenediamine	1760-24-3	>= 2.5 - < 5
tris(dodecylbenzenesulphonato-O)(propan-2-olato)titanium	tris(dodecylbenzenesulphonato-O)(propan-2-olato)titanium	61417-55-8	>= 1 - < 3

## 4. FIRST AID MEASURES

General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.

# SAFETY DATA SHEET

## Sika® Aktivator-100



Version  
4.1

Revision Date:  
19.09.2025

SDS Number (Internal):  
000000033123

Date of last issue: 10.08.2023  
Date of first issue: 22.12.2015

---

- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Continue rinsing eyes during transport to hospital.  
Remove contact lenses.  
Keep eye wide open while rinsing.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : Risk of serious damage to the lungs (by aspiration).  
irritant effects  
sensitising effects  
Aspiration may cause pulmonary oedema and pneumonitis.  
Allergic reactions  
Excessive lachrymation  
Dermatitis  
Loss of balance  
Vertigo  
See Section 11 for more detailed information on health effects and symptoms.  
May be fatal if swallowed and enters airways.  
Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.  
May cause cancer.
- Notes to physician : Treat symptomatically.
- 

### 5. FIREFIGHTING MEASURES

#### Suitable and unsuitable extinguishing media

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : Water  
High volume water jet
-

# SAFETY DATA SHEET

## Sika® Aktivator-100



Version 4.1	Revision Date: 19.09.2025	SDS Number (Internal): 000000033123	Date of last issue: 10.08.2023 Date of first issue: 22.12.2015
----------------	------------------------------	--	---

---

- Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.  
Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : No hazardous combustion products are known
- Specific extinguishing methods : Use water spray to cool unopened containers.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
- 

### 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Remove all sources of ignition.  
Deny access to unprotected persons.
- Environmental precautions : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
- 

### 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Use explosion-proof equipment.  
Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.  
Take precautionary measures against electrostatic discharges.
- Advice on safe handling : Do not breathe vapours or spray mist.  
Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
-

# SAFETY DATA SHEET

## Sika® Aktivator-100



Version  
4.1

Revision Date:  
19.09.2025

SDS Number (Internal):  
000000033123

Date of last issue: 10.08.2023  
Date of first issue: 22.12.2015

Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharge.  
Open drum carefully as content may be under pressure.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).  
Follow standard hygiene measures when handling chemical products

Conditions for safe storage : Store in original container.  
Store in cool place.  
Keep in a well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Store in accordance with local regulations.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ethanol	64-17-5	TWA	1,000 ppm	KR OEL
	Further information: Sufficient evidence of carcinogenicity in humans, Carcinogenic classification 1A for drinking alcohol only			

Other ingredients, which are listed in section 3 but not listed in this section, do not have established occupational exposure limit values.

#### Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
methanol	67-56-1	TWA	200 ppm	KR OEL
	Further information: Substances designated by 'Skin' may be absorbed into the bloodstream through the skin, mucous membrane and eye and contribute to the overall effect. (Skin notation does not apply to the skin irritant)			
		STEL	250 ppm	KR OEL
		TWA	200 ppm	KR PEL
		STEL	250 ppm	KR PEL

**Personal protective equipment. Among the following personal protective equipment, the PPEs which require safety certification need to be certified by KOSHA.**

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

# SAFETY DATA SHEET

## Sika® Aktivator-100



Version  
4.1

Revision Date:  
19.09.2025

SDS Number (Internal):  
000000033123

Date of last issue: 10.08.2023  
Date of first issue: 22.12.2015

contained breathing apparatus must be used.

- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.  
When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Colour : colourless
- Odour : hydrocarbon-like
- Odour Threshold : No data available
- pH : Not applicable substance/mixture is non-soluble (in water)
- Melting point/ range / Freezing point : No data available
- Boiling point/boiling range : ca. 78 °C (172 °F)
- Flash point : ca. -4 °C (25 °F)  
(Method: closed cup)
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available

#### Upper/lower flammability or explosive limits

- Upper explosion limit / Upper flammability limit : 7.4 %(V)
- Lower explosion limit / Lower flammability limit : 1.1 %(V)
- Vapour pressure : 58 hPa

# SAFETY DATA SHEET

## Sika® Aktivator-100



Version  
4.1

Revision Date:  
19.09.2025

SDS Number (Internal):  
000000033123

Date of last issue: 10.08.2023  
Date of first issue: 22.12.2015

---

Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Density	:	ca. 0.727 g/cm <sup>3</sup> (20 °C)
Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	< 20.5 mm <sup>2</sup> /s ( 40 °C (104 °F))
Explosive properties	:	No data available
Oxidizing properties	:	No data available

---

### 10. STABILITY AND REACTIVITY

Chemical stability and possibility of hazardous reactions	:	Reactivity: No dangerous reaction known under conditions of normal use. Chemical stability: The product is chemically stable. Possibility of hazardous reactions: Stable under recommended storage conditions. Possibility of hazardous reactions: Vapours may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	No data available
Hazardous decomposition products	:	methanol

---

### 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : No data available

#### Health hazard information

##### Acute toxicity

No data available

# SAFETY DATA SHEET

## Sika® Aktivator-100



Version  
4.1

Revision Date:  
19.09.2025

SDS Number (Internal):  
000000033123

Date of last issue: 10.08.2023  
Date of first issue: 22.12.2015

---

### Components:

#### **N-(3-(trimethoxysilyl)propyl)ethylenediamine:**

Acute oral toxicity : LD50 Oral (Rat): 2,995 mg/kg

#### **Skin corrosion/irritation**

Causes skin irritation.

#### **Serious eye damage/eye irritation**

Causes serious eye irritation.

#### **Respiratory or skin sensitisation**

#### **Respiratory sensitisation**

No data available

#### **Skin sensitisation**

May cause an allergic skin reaction.

#### **Carcinogenicity**

May cause cancer.

### Components:

#### **Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

No data available

#### **ethanol:**

May cause cancer.

#### **N-(3-(trimethoxysilyl)propyl)ethylenediamine:**

No data available

#### **tris(dodecylbenzenesulphonato-O)(propan-2-olato)titanium:**

No data available

#### **Germ cell mutagenicity**

No data available

### Components:

#### **Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

No data available

#### **ethanol:**

No data available

#### **N-(3-(trimethoxysilyl)propyl)ethylenediamine:**

No data available

# SAFETY DATA SHEET

## Sika® Aktivator-100



Version  
4.1

Revision Date:  
19.09.2025

SDS Number (Internal):  
000000033123

Date of last issue: 10.08.2023  
Date of first issue: 22.12.2015

---

**tris(dodecylbenzenesulphonato-O)(propan-2-olato)titanium:**

No data available

**Reproductive toxicity**

No data available

**Components:**

**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

No data available

**ethanol:**

No data available

**N-(3-(trimethoxysilyl)propyl)ethylenediamine:**

No data available

**tris(dodecylbenzenesulphonato-O)(propan-2-olato)titanium:**

No data available

**STOT - single exposure**

May cause drowsiness or dizziness.

**STOT - repeated exposure**

No data available

**Repeated dose toxicity**

No data available

**Aspiration toxicity**

May be fatal if swallowed and enters airways.

**Experience with human exposure**

No data available

**Toxicology, Metabolism, Distribution**

No data available

**Neurological effects**

No data available

**Further information**

No data available

---

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity**

No data available

# SAFETY DATA SHEET

## Sika® Aktivator-100



Version  
4.1

Revision Date:  
19.09.2025

SDS Number (Internal):  
000000033123

Date of last issue: 10.08.2023  
Date of first issue: 22.12.2015

---

### Persistence and degradability

No data available

### Bioaccumulative potential

No data available

### Mobility in soil

No data available

### Other adverse effects

#### Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Toxic to aquatic life with long lasting effects.

---

## 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Send to a licensed waste management company.  
  
The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.

Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

### Disposal precautions

Dispose of contents and container according to wastes control act.

---

## 14. TRANSPORT INFORMATION

### International Regulations

#### UNRTDG

UN number : UN 1866  
Proper shipping name : RESIN SOLUTION  
Class : 3  
Packing group : II  
Labels : 3  
Environmentally hazardous : yes

#### IATA-DGR

UN/ID No. : UN 1866  
Proper shipping name : Resin solution  
Class : 3  
Packing group : II

---

# SAFETY DATA SHEET

## Sika® Aktivator-100



Version  
4.1

Revision Date:  
19.09.2025

SDS Number (Internal):  
000000033123

Date of last issue: 10.08.2023  
Date of first issue: 22.12.2015

Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 364  
Packing instruction (passenger aircraft) : 353  
Environmentally hazardous : yes

### IMDG-Code

UN number : UN 1866  
Proper shipping name : RESIN SOLUTION  
Class : 3  
Packing group : II  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : yes

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### National Regulations

Refer to section 15 for specific national regulation.

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

---

## 15. REGULATORY INFORMATION

### National regulatory information

#### Regulation under the Occupational Safety and Health Act

#### Harmful Substances Prohibited from Manufacturing

Not applicable

#### Harmful Substances Required Permission for Manufacture

Not applicable

#### Harmful Agents to be kept below Occupational Exposure Limits

Chemical name	CAS-No.
Ethyl alcohol	64-17-5

#### Harmful Agents Required to be kept below Permission Levels

Not applicable

#### Hazardous substances requiring management

Not applicable

#### Special Management Materials

Not applicable

# SAFETY DATA SHEET

## Sika® Aktivator-100



Version  
4.1

Revision Date:  
19.09.2025

SDS Number (Internal):  
000000033123

Date of last issue: 10.08.2023  
Date of first issue: 22.12.2015

### Controlled Substances Subject to Environment Monitoring

Not applicable

### Controlled Substances Subject to Health Examination

Not applicable

### Hazardous Substances Subject to Process Safety Management (PSM) Reporting Obligation

Chemical name/Classification	Manufacturing or handling quantity	Storage quantity
Flammable liquids	5,000 kg	200,000 kg

### K-OSHA Hazardous Substances (Occupational Safety and Health Regulations, Table 1)

Category
Flammable liquid
Corrosive substances

### K-OSHA Hazardous Substances (Occupational Safety and Health Regulations, Table 9)

Category	Manufacturing or handling quantity
Flammable liquid	400 litre
Corrosive substances	300 kilogram

### Regulation under the Chemicals Control Act

#### Toxic Chemicals

Not applicable

#### Restricted Chemicals

Not applicable

#### Prohibited Chemicals

Not applicable

#### Toxic Release Inventory

Not applicable

#### Accident Precaution Chemicals

Not applicable

### Dangerous Substances Safety Management Act

Classification : Group 4, Flammable liquids, Type 1 petroleum, Water insoluble liquid

Hazard rank : Hazardous rank II

Designated Quantity : 200 litre

Safety Warning : Keep away from fire

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors : Not applicable

### 라. Wastes Control Act

Industrial general wastes

Follow article 13 of the act to dispose the product waste

# SAFETY DATA SHEET

## Sika® Aktivator-100



Version  
4.1

Revision Date:  
19.09.2025

SDS Number (Internal):  
000000033123

Date of last issue: 10.08.2023  
Date of first issue: 22.12.2015

### Other requirements in domestic and other countries

#### The components of this product are reported in the following inventories:

ENCS : On the inventory, or in compliance with the inventory  
ISHL : Not in compliance with the inventory  
KECI : On the inventory, or in compliance with the inventory


## 16. OTHER INFORMATION

Issuing date : 22.12.2015

#### Revision number and date

Number of Revision : 4.1  
Revision Date : 19.09.2025  
Date format : yyyy/mm/dd

#### NFPA:



#### Full text of other abbreviations

KR OEL : Harmful Agents to be kept below Occupational Exposure Limits  
KR PEL : Harmful Agents Required to be kept below Permission Levels  
KR OEL / TWA : Time Weighted Average  
KR OEL / STEL : Short Term Exposure Limit  
KR PEL / TWA : TWA  
KR PEL / STEL : STEL  
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road  
CAS : Chemical Abstracts Service

# SAFETY DATA SHEET

## Sika® Aktivator-100



Version 4.1	Revision Date: 19.09.2025	SDS Number (Internal): 000000033123	Date of last issue: 10.08.2023 Date of first issue: 22.12.2015
----------------	------------------------------	--	---

---

DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

KR / EN