

PRODUCT DATA SHEET

SikaCeram® CleanGrout

Cementitious floor and wall tile grout for joints 1–8 mm

DESCRIPTION

SikaCeram® CleanGrout is a cementitious powder floor and wall tile grout for use in joints from 1–8 mm in width. Additives contained in the powder provide protection against mould, bacterial and fungal growth while maintaining a colour stable, abrasion resistant, water repellent durable finish.

USES

Grouting the following tile types:

- Ceramic / Earthenware
- Glass mosaic
- Marble and other natural stones
- Porcelain

Grouting tiles for the following high performance and demanding applications:

- Swimming pools (excluding sea water)
- Heated floors
- Commercial / Industrial / Residential environments
- Facades / Interior and exterior use

CHARACTERISTICS / ADVANTAGES

- Floor and wall application
- Water-repellent
- Abrasion resistant
- High degree of hardness
- UV resistant
- Frost proof
- Contains mould protection

APPROVALS / CERTIFICATES

KS L ISO 13007-4 : 2011 / ISO 846 : 2019

PRODUCT INFORMATION

Product declaration	EN 13888: CG2WA				
Composition	Polymer modified, portland cement based, with selected fine silica/quartz sand, water retainers and other special additives.				
Packaging	5 kg bags. Refer to current price list for packaging variations.				
Shelf life	24 months from date of production.				
Storage conditions	The product must be stored in original, unopened and undamaged packaging in dry conditions at temperatures between +5 °C and +30 °C.				
Appearance and colour	Colours:				
	White	Light Grey	Silver	Manhattan	Ice
	Grey	Ash	Anthracite	Graphite	Total black
	Pergamon	Jasmine	Anemone	Beige	Pine
	Caramel	Maple wood	Dove Grey	Light Sand	Sand
	Cedar	Beech wood	Walnut	Oak wood	Brown
	Terracotta	Amaranth	Ruby	Dark Brown	Mahogany

TECHNICAL INFORMATION

APPLICATION INFORMATION

D = Tile width (cm)

Pot Life	~2 hours
----------	----------

Waiting time	Before grouting on floor tiles laid with	
	Normal-setting adhesive	24–36 hours
	Fast-setting adhesive	4–6 hours
	Thick-bed (traditional) adhesive	8–10 days
	Before grouting on wall tiles laid with	
	Normal-setting adhesive	4–6 hours
	Fast-setting adhesive	2 hours
	Above times are indicative. Always consult the appropriate tile adhesive Product Data Sheet.	
	Applied product ready for use	
	Use	Waiting time
	Pedestrian traffic	24–36 hours
	Full traffic	~14 days
	Water immersion	~21 days

BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

IMPORTANT CONSIDERATIONS

- Do not exceed the recommended amount of water in the mix. The mix must never be fluid.
- The product is not suitable for chemical exposure. Use an epoxy grout from the range of SikaCeram® products.
- Prevent contact of freshly applied material with water (including rain), except during cleaning operations. Also prevent exposure with excess atmospheric humidity / condensation or residual moisture in the substrate etc.
- Avoid significant temperature variations during application and setting times, as well as excessive draughts, forced ventilation or winds.
- Excess water and ventilation, temperature variations, application on very porous tiles or on substrates leading to rapid water absorption etc. can result in colour shade variations.
- When coloured grout is applied for aesthetics such as on polished porcelain or natural stone tiles, always carry out cleanability testing on a small area prior to full application.
- On highly absorbent tiles, it is always recommended to thoroughly pre-dampen the surface before grouting.
- Always apply SikaCeram® CleanGrout in a continuous operation and do not interrupt for more than two hours in the same room or area of tiling.
- Premature exposure to water or excess water in the mix can result in white efflorescence on the grout surface.
- Avoid application in direct sunlight to avoid cracking in the joint.
- To avoid grout removal from joint, ensure grout has set sufficiently before carrying out the tile cleaning procedure.
- Do not add anything to the product that is not specified in this Product Data Sheet.

- Do not use for any applications not explicitly described in this Product Data Sheet.

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

EQUIPMENT

Select the most appropriate equipment required for the project:

Mixing equipment

- Low speed electric single or double paddle mixer (500 rpm) with spiral paddle

Application equipment

- Grout spreader
- Squeegee
- Grouting float/trowel.
- Sponge
- Soft cloth
- Grout finishing tool

SUBSTRATE QUALITY / PRE-TREATMENT

- Check joints are dry, clean, and clear of excess adhesive, contaminants and tile joint spacers. Remove from joint before grout application.
- For applications in hot climates / environments, or on absorbent substrates, thoroughly pre-dampen the surface immediately prior to product application.
- Avoid any ponding / standing water on the surface.
- Surface must not be damp to touch.

MIXING

IMPORTANT

Avoid over-mixing to minimise air entrainment.

IMPORTANT

Do not add additional water into the mixed product

during or after mixing.

IMPORTANT

Do not exceed the recommended amount of water in the mix. The mix must never be fluid.

Note: For high-performance and demanding applications, such as: heavily trafficked floors, exposed facades, swimming pools or for additional flexibility. Replace water with a solution of SikaCeram® Latex-Grout (Refer to the individual Product Data Sheet)

Requirement: Use a low speed electric single paddle mixer (500 rpm) with a spiral mixing paddle.

1. Pour the recommended amount of clean cold water into a clean mixing container.
2. Gradually add SikaCeram® CleanGrout powder to the water while mixing.
3. Mix thoroughly until a uniformly coloured, smooth mix is achieved.
4. Do not mix for 2–3 minutes to allow mixed product to 'mature'.
5. Remix for ~30 seconds.

APPLICATION

IMPORTANT

Check adhesive has fully set before grouting.

Note: When using SikaCeram® LatexGrout instead of water in the grout mix. Immediately polish the tiles after the initial cleaning with a damp sponge.

1. Apply SikaCeram® CleanGrout using a grout spreader, squeegee or grouting float/trowel.
2. Completely fill and compact the joints uniformly.
3. If required, finish grout with a grout finishing tool while grout is wet.
4. Using the same spreader/ float, remove excess grout from the tile surfaces moving the tool diagonally across the joints.
5. When the grout is touch dry. Use a damp sponge or sponge float to clean the tile surfaces. Clean sponge regularly with clean water.
6. When the grout has set hard enough in the joint (finger-nail hard). Polish the tile surfaces by wiping with a clean, soft dry cloth.

CLEANING OF EQUIPMENT

Clean all tools and application equipment with water after use. Hardened material can only be removed mechanically.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Korea Ltd.

135 gil 16, Nonhyun-ro
Gangnam-ku, Seoul, Korea
Tel : +82 2 6912 1500
Fax: +82 2 6912 1555
web: <http://kor.sika.com>



Product Data Sheet

SikaCeram® CleanGrout
January 2022, Version 04.01
021720100000000017

SikaCeramCleanGrout-en-KR-(01-2022)-4-1.pdf

