

# Sikafloor® - 263 SL

2 Self-smoothing / broadcast

■ Sikafloor®- 263 SL , 2  
 ■  
 ■ Broadcast (wet process area)

■ /  
 ■ (Highly fillable)  
 ■  
 ■  
 ■  
 ■  
 ■  
 ■  
 ■ 가

■ /  
 - Part A:  
 - Part B:  
 Ral 7030, 7032, 7035, 7037, 7040  
 가

Part A:	220 kg		
Part B:	177 kg	59 kg	
Part A+B:	1	Part A (220 kg) + 1	Part B (59 kg) = 279 kg
	3	Part A (220 kg) + 1	Part B(177 kg) = 837 kg

/ +5 +30  
 12

Part A:	~ 1.50kg/ℓ	(DIN EN ISO 2811-1)
Part B:	~ 1.00kg/ℓ	
:	~ 1.43kg/ℓ	
1:1	~ 1.84kg/ℓ	
+23		



~ 100% ( ) / ~100% ( )  
 : ~ 60 N/mm<sup>2</sup> (28 /+23 ) (EN 196-1)  
 : ~ 30 N/mm<sup>2</sup> (28 /+23 ) (EN 196-1)  
 >1.5N/mm<sup>2</sup> ( ) (ISO 1542)  
**Shore D hardness** 76 (7 /+23 ) (EN ISO 868)  
 70mg(CS 10/1000/1000) (7 /+23 ) (EN ISO 5470(Taber Abrader Test))

*	(dry heat)
	+50
( 7 )	+80
( 12 )	+100

\* ( ) +80

\* 가 가

Self-smoothing system ( : 1.5-3.0 mm)

: 1 x Sikafloor-161

: 1 x Sikafloor-263 SL + quartz sand(0.1~0.3 mm)

Broadcast system ( : 4 mm)

: 1 x Sikafloor-161

: 1 x Sikafloor-263 SL + quartz sand(0.1~0.3 mm)

: quartz sand(0.4-0.7 mm)

: 1 x Sikafloor-264

/

	Sikafloor-161	0.35~0.55 kg/ m <sup>2</sup>
( )	Sikafloor-161	Sikafloor-161 PDS
Self-smoothing wearing course ( ~1.5~3.0mm)	1 pbw Sikafloor-263 SL + 1 pbw (0.1~0.3mm)	1.9kg/ m <sup>2</sup> (0.95kg/ m <sup>2</sup> binder + 0.95 kg/ m <sup>2</sup> )/ 1mm
Broadcast System ( ~4.0 mm)	1 pbw Sikafloor-263 SL + 1 pbw (0.1-0.3mm)+ 0.4~0.7mm + Sikafloor 264	2.00 kg/ m <sup>2</sup> 2.00 kg/ m <sup>2</sup> ~6.0 kg/ m <sup>2</sup> ~0.7 kg/ m <sup>2</sup>

가



# Construction

( 25N/mm<sup>2</sup>)

1.5N/mm<sup>2</sup>

( ),

Sikafloor, SikaDur,

SikaGard

(high spot)

+10 / +30

+10 / +30

pbw 4%

: Sika-Tramex

CM-

ASTM( )

가

80%

!

3

( , blooming -

)

Part A : Part B = 79 : 21 ( )

Part A

. Part A part B

2

. Part A part B

2

Sikafloor®- 263 SL

(stirrer, 300-400rpm)

pbw

4%

(T.M.B.)

Sikafloor

EpoCem



Sikafloor-161

(smooth)

Sikafloor®- 263 SL

Broadcast

Sikafloor®- 263 SL

15 (+20°C) 30 (+20°C)

quartz sand

Thinner C

가 가

가 (potlife)

+ 10	~ 50
+ 20	~ 25
+ 30	~ 15

/

Sikafloor-161 Sikafloor®- 263 SL

+ 10	24	3
+ 20	12	2
+ 30	8	1

Sikafloor®- 263 SL Sikafloor-263 SL

+ 10	30	3
+ 20	24	2
+ 30	16	1

Sikafloor®- 263 SL

/

Sikafloor®- 263 SL 24

Broadcast system

Sikafloor-161



PPW-Polyplan-Werkzeuge GmbH, Phone: +49 40/5597260, [www.polyplan.com](http://www.polyplan.com).

: Large-Surface Scraper No. 565, Toothed blades No.25

: Trowel No. 999      Adhesive Spreader No.777, Toothed blades No.23

Sikafloor®- 263 SL

가 , ,

가

	가	가	
+ 10	~ 72	~ 6	~ 10
+ 20	~ 24	~ 4	~ 7
+ 30	~ 18	~ 2	~ 5

( , , , )

가

) (M.S.D.S)

Sika

Sika



# Construction

가 ( )

EU 2004/42 EU-Directive 2004 , VOC (Product category IIA / j type **sb**) 550 / 500  
 VOC-Decopaint g/l (2007 / 2010 ) . Sikafloor-263 SL VOC < 500 g/l .  
 Directive

Sika Korea Ltd. KS/ISO 9002,14001



\* Sika Korea  
 \* Sika Korea 가 가

Visit our website at <http://www.sikakorea.co.kr>

Sika Korea Ltd.  
 303 324-1  
 (.137-897)  
 Tel. 02-6912-1500  
 Fax. 02-6912-1555

Sika Korea Ltd. /  
 304 ( 2 )  
 (.456-843)  
 Tel. 031-8056-7777  
 Fax. 031-8056-7788

Sika Korea Ltd. /  
 304 ( 2 )  
 (.456-843)  
 Tel. 031-8056-7777  
 Fax. 031-8056-7766

