

Sikafloor® - 264

2



Sikafloor®- 264 , 2 , .



(, , ,)

■ Broadcast Seal



/



가



/

- Part A:

- Part B:

Ral 7030, 7032, 7035, 7037, 7040

가

Part A : 220 kg

Part B : 177 kg 59 kg

Part A+B : 1 Part A (220 kg) + 1 Part B (59 kg) = 279 kg

3 Part A (220 kg) + 1 Part B(177 kg) = 837 kg

/

+5 +30

12



Part A: ~ 1.64kg/ℓ (DIN EN ISO 2811-1)
 Part B: ~ 1.00kg/ℓ
 : ~ 1.40kg/ℓ
 +23
 ~ 100%() / ~100%()\

: ~ 60 N/mm² (28 /+23) (EN 196-1)
 : ~ 30 N/mm² (28 /+23) (EN 196-1)
 >1.5N/mm² () (ISO 1542)
Shore D hardness 76 (7 /+23) (EN ISO 868)
 70mg(CS 10/1000/1000) (7 /+23) (EN ISO 5470(Taber Abrader Test))

*	(dry heat)
	+50
(7)	+80
(12)	+100

* () +80
 * 가 가

(Roller coating)

: 1 x Sikafloor-161()
 : 2 x Sikafloor-264
 : Sikafloor-161

Broadcast system (: 4 mm)

: 1 x Sikafloor-161
 : 1 x Sikafloor-263 SL + quartz sand(0.1~0.3 mm)
 : quartz sand(0.4-0.7 mm)
 : 1 x Sikafloor-264



	Sikafloor-161	0.35~0.55 kg/ m ²
()	Sikafloor-161	Sikafloor-161 PDS
	2 x Sikafloor 264	0.25 ~0.3 kg /m ² 1
Textured	1~2 x Sikafloor®- 264+ Extender T	0.5~0.8 kg/m ² / 1
Textured ()	10 pbw Sikafloor®- 264+ Extender T + 1 pbw quartz sand (0.1~0.5mm)	0.5~0.8 kg /m ² 0.05~0.07 kg /m ²
Broadcast System (~4.0 mm)	1 pbw Sikafloor-263 SL + 1 pbw (0.1-0.3mm)+ 0.4~0.7mm + Sikafloor®- 264	2.00 kg/ m ² 2.00 kg/ m ² ~6.0 kg/ m ² ~0.7 kg/ m ²

가 (25N/mm²)
1.5N/mm² () ,

SikaGard Sikafloor, SikaDur,
(high spots)





/

+10 / +30
 +10 / +30
 pbw 4%
 : Sika-Tramex CM-
 ASTM() 가
 80%

3

. (, blooming -)

Part A : Part B = 79 : 21 ()

Part A . Part A part B
 2

Sikafloor®- 264 (stirrer, 300-400rpm)

/

pbw 4% (T.M.B.) Sikafloor
 EpoCem

. Sikafloor-161

Sikafloor®- 264 short-piled

Seal (sealer) short-piled

Thinner C

가 가

가 (potlife)

+ 10	~ 50
+ 20	~ 25
+ 30	~ 15



/

Sikafloor-161 Sikafloor®- 264

+ 10	24	3
+ 20	12	2
+ 30	8	1

Sikafloor-263 SL Sikafloor®- 264

+ 10	30	3
+ 20	24	2
+ 30	16	1

:

/

Sikafloor-263 SL

Sikafloor®- 264 24

Broadcast system

Sikafloor-161

: PPW-Polyplan-Werkzeuge GmbH, Phone: +49 40/5597260, www.polyplan.com.

:

: Large-Surface Scrapper No. 565, Toothed blades No.25

:

: Trowel No. 999 Adhesive Spreader No.777, Toothed blades No.23

Sikafloor®- 264

가 , ,

가

	가	가	
+ 10	~ 72	~ 6	~ 10
+ 20	~ 24	~ 4	~ 7
+ 30	~ 18	~ 2	~ 5

:





(, , ,)

가

(M.S.D.S)

Sika

Sika

3

가

()

EU 2004/42 EU-Directive 2004 , VOC (Product category IIA / j type **sb**) 550 / 500
 VOC-Decopaint g / l (2007 / 2010) . Sikafloor-264 VOC < 500 g/l
 Directive

Sika Korea Ltd. KS/ISO 9002,14001



* Sika Korea
 * Sika Korea 가 가

Visit our website at <http://www.sikakorea.co.kr>

Sika Korea Ltd.
 303
 (.137-897)
 Tel. 02-6912-1500
 Fax. 02-6912-1555

324-1

Sika Korea Ltd. /
 304 (2)
 (.456-843)
 Tel. 031-8056-7777
 Fax. 031-8056-7788

Sika Korea Ltd. /
 304 (2)
 (.456-843)
 Tel. 031-8056-7777
 Fax. 031-8056-7766

