

SAFETY DATA SHEET

SikaForce®-050 (B)



Version
3.0

Revision Date:
27.03.2024

SDS Number (Internal):
000000217609

Date of last issue: 28.03.2022
Date of first issue: 08.11.2019

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : SikaForce®-050 (B)

Recommended use of the chemical and restrictions on use

Product use : Sealant/adhesive

Manufacturer or supplier's details

Company : Sika Korea Ltd.
724, Anseongmatchum-daero
Miyang-myeon
Anseong-si
Gyeonggi-do
Korea

Telephone : +82-31-8056-7777

Emergency telephone number : +82-31-8056-7777

E-mail address : ehs@kr.sika.com

Telefax : +82-31-8056-7788

2. HAZARDS IDENTIFICATION

GHS Classification

Acute toxicity (Inhalation) : Category 4

Skin corrosion/irritation : Category 2

Serious eye damage/eye irritation : Category 2

Respiratory sensitisation : Category 1

Skin sensitisation : Category 1

Carcinogenicity : Category 2

Specific target organ toxicity - single exposure : Category 3 (Respiratory system, Central nervous system)

Specific target organ toxicity - repeated exposure : Category 2

GHS label elements

SAFETY DATA SHEET

SikaForce®-050 (B)



Version
3.0

Revision Date:
27.03.2024

SDS Number (Internal):
000000217609

Date of last issue: 28.03.2022
Date of first issue: 08.11.2019

Hazard pictograms



Signal word

: Danger

Hazard statements

: H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.
H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

: **Prevention:**

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe mist or vapours.
P264 Wash the contact area thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P284 Wear respiratory protection.

: **Response:**

P302 + P352 IF ON SKIN: Wash with plenty of water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P321 Specific treatment (see supplemental first aid instructions on this label).
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.
P362 + P364 Take off contaminated clothing and wash it before reuse.

SAFETY DATA SHEET

SikaForce®-050 (B)



Version
3.0

Revision Date:
27.03.2024

SDS Number (Internal):
000000217609

Date of last issue: 28.03.2022
Date of first issue: 08.11.2019

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents and container according to wastes control act.

Other hazards which do not result in classification

No data available

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	Common Name	CAS-No.	Concentration (% w/w)
Diphenylmethanediisocyanate, isomeres and homologues	Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9	$\geq 70 - < 75$
4,4'-methylenediphenyl diisocyanate	4,4'-methylenediphenyl diisocyanate	101-68-8	$\geq 5 - < 10$
o-(p-isocyanatobenzyl)phenyl isocyanate	o-(p-isocyanatobenzyl)phenyl isocyanate	5873-54-1	$\geq 5 - < 10$

4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.

In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.

If inhaled : Move to fresh air.
Consult a physician after significant exposure.

SAFETY DATA SHEET

SikaForce®-050 (B)



Version
3.0

Revision Date:
27.03.2024

SDS Number (Internal):
000000217609

Date of last issue: 28.03.2022
Date of first issue: 08.11.2019

If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Obtain medical attention.

Most important symptoms and effects, both acute and delayed : irritant effects
sensitising effects
Asthmatic appearance
Cough
Respiratory disorder
Allergic reactions
Excessive lachrymation
Headache
Dermatitis
See Section 11 for more detailed information on health effects and symptoms.
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
Harmful if inhaled.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause respiratory irritation.
May cause drowsiness or dizziness.
Suspected of causing cancer.
May cause damage to organs through prolonged or repeated exposure.

Notes to physician : Treat symptomatically.

5. FIREFIGHTING MEASURES

Suitable and unsuitable extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Hazardous combustion products : No hazardous combustion products are known

Specific extinguishing methods : Standard procedure for chemical fires.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency measures : Use personal protective equipment.
Deny access to unprotected persons.

SAFETY DATA SHEET

SikaForce®-050 (B)



Version 3.0 Revision Date: 27.03.2024 SDS Number (Internal): 00000217609 Date of last issue: 28.03.2022
Date of first issue: 08.11.2019

gency procedures

Environmental precautions : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Provide sufficient air exchange and/or exhaust in work rooms.
Follow standard hygiene measures when handling chemical products

Conditions for safe storage : Store in original container.
Keep in a well-ventilated place.
Observe label precautions.
Store in accordance with local regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9	TWA	0.005 ppm	KR OEL
	Further information: Limited evidence of carcinogenicity in humans or animals, which is not sufficiently convincing to place the substance in Category 1			
		TWA	0.005 ppm	KR PEL
		TWA	0.005 ppm	ACGIH
4,4'-methylenediphenyl diisocyanate	101-68-8	TWA	0.005 ppm	KR OEL
	Further information: Limited evidence of carcinogenicity in hu-			

SAFETY DATA SHEET

SikaForce®-050 (B)



Version
3.0

Revision Date:
27.03.2024

SDS Number (Internal):
000000217609

Date of last issue: 28.03.2022
Date of first issue: 08.11.2019

	mans or animals, which is not sufficiently convincing to place the substance in Category 1			
		TWA	0.005 ppm	KR PEL
		TWA	0.005 ppm	ACGIH
o-(p-isocyanatobenzyl)phenyl isocyanate	5873-54-1	TWA	0.005 ppm	KR OEL
	Further information: Limited evidence of carcinogenicity in humans or animals, which is not sufficiently convincing to place the substance in Category 1			
		TWA	0.005 ppm	KR PEL
		TWA	0.005 ppm	ACGIH

Other ingredients, which are listed in section 3 but not listed in this section, do not have established occupational exposure limit values.

Personal protective equipment. Among the following personal protective equipment, the PPEs which require safety certification need to be certified by KOSHA.

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : paste
- Colour : brown
- Odour : slight
- Odour Threshold : No data available

SAFETY DATA SHEET

SikaForce®-050 (B)



Version
3.0

Revision Date:
27.03.2024

SDS Number (Internal):
000000217609

Date of last issue: 28.03.2022
Date of first issue: 08.11.2019

pH : Not applicable substance/mixture is non-soluble (in water)

Melting point/range / Freezing point : No data available

Boiling point/boiling range : No data available

Flash point : > 200 °C (392 °F)
(Method: closed cup)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper/lower flammability or explosive limits

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapour pressure : 0.01 hPa

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Density : ca. 1.22 g/cm³ (20 °C)

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : > 20.5 mm²/s (40 °C (104 °F))

Explosive properties : No data available

Oxidizing properties : No data available

10. STABILITY AND REACTIVITY

Chemical stability and possibility of hazardous reactions : No dangerous reaction known under conditions of normal use.
The product is chemically stable.
No hazards to be specially mentioned.

SAFETY DATA SHEET

SikaForce®-050 (B)



Version
3.0

Revision Date:
27.03.2024

SDS Number (Internal):
000000217609

Date of last issue: 28.03.2022
Date of first issue: 08.11.2019

Conditions to avoid : No data available

Incompatible materials : No data available

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : No data available

Health hazard information

Acute toxicity

Harmful if inhaled.

Components:

Diphenylmethanediisocyanate, isomeres and homologues:

Acute oral toxicity : LD50 Oral (Rat): > 10,000 mg/kg

Acute inhalation toxicity : LC50: 1.5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Expert judgement
Assessment: The component/mixture is moderately toxic after short term inhalation.

Acute dermal toxicity : LD50 Dermal (Rabbit): > 9,400 mg/kg

4,4'-methylenediphenyl diisocyanate:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50: 1.5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Expert judgement

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin sensitisation

May cause an allergic skin reaction.

SAFETY DATA SHEET

SikaForce®-050 (B)



Version
3.0

Revision Date:
27.03.2024

SDS Number (Internal):
000000217609

Date of last issue: 28.03.2022
Date of first issue: 08.11.2019

Carcinogenicity

Suspected of causing cancer.

Components:

Diphenylmethanediisocyanate, isomeres and homologues:

No data available

4,4'-methylenediphenyl diisocyanate:

Suspected of causing cancer.

o-(p-isocyanatobenzyl)phenyl isocyanate:

Suspected of causing cancer.

Germ cell mutagenicity

Components:

Diphenylmethanediisocyanate, isomeres and homologues:

No data available

4,4'-methylenediphenyl diisocyanate:

No data available

Genotoxicity in vivo : Species: Bacteria
Method: OECD Test Guideline 471
Result: negative

Method: TA98

Method: TA100

Method: TA1535

Method: TA1537

o-(p-isocyanatobenzyl)phenyl isocyanate:

No data available

Reproductive toxicity

Components:

Diphenylmethanediisocyanate, isomeres and homologues:

No data available

4,4'-methylenediphenyl diisocyanate:

No data available

SAFETY DATA SHEET

SikaForce®-050 (B)



Version
3.0

Revision Date:
27.03.2024

SDS Number (Internal):
000000217609

Date of last issue: 28.03.2022
Date of first issue: 08.11.2019

o-(p-isocyanatobenzyl)phenyl isocyanate:

No data available

STOT - single exposure

May cause respiratory irritation.
May cause drowsiness or dizziness.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Repeated dose toxicity

No data available

Aspiration toxicity

No data available

Experience with human exposure

No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information

No data available

12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Diphenylmethanediisocyanate, isomeres and homologues:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 1,000 mg/l
Exposure time: 96 h

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): > 1,640 mg/l
Exposure time: 72 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

SAFETY DATA SHEET

SikaForce®-050 (B)



Version
3.0

Revision Date:
27.03.2024

SDS Number (Internal):
000000217609

Date of last issue: 28.03.2022
Date of first issue: 08.11.2019

Other adverse effects

Product:

Additional ecological information : There is no data available for this product.

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

Disposal precautions

Dispose of contents and container according to wastes control act.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable

IATA-DGR

UN/ID No. : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
Packing instruction (cargo aircraft) : Not applicable
Packing instruction (passenger aircraft) : Not applicable

IMDG-Code

UN number : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
EmS Code : Not applicable

SAFETY DATA SHEET

SikaForce®-050 (B)



Version
3.0

Revision Date:
27.03.2024

SDS Number (Internal):
000000217609

Date of last issue: 28.03.2022
Date of first issue: 08.11.2019

Marine pollutant : Not applicable

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

Refer to section 15 for specific national regulation.

Special precautions for user

Not applicable

15. REGULATORY INFORMATION

National regulatory information

Regulation under the Occupational Safety and Health Act

Harmful Substances Prohibited from Manufacturing

Not applicable

Harmful Substances Required Permission for Manufacture

Not applicable

Harmful Agents to be kept below Occupational Exposure Limits

Chemical name	CAS-No.
Methylene bisphenyl isocyanate	9016-87-9
Methylene bisphenyl isocyanate	101-68-8
Methylene bisphenyl isocyanate	5873-54-1

Harmful Agents Required to be kept below Permission Levels

Chemical name	CAS-No.
Methylene bis(phenyl isocyanate)	9016-87-9
Methylene bis(phenyl isocyanate)	101-68-8
Methylene bis(phenyl isocyanate)	5873-54-1

Hazardous substances requiring management

Chemical name	CAS-No.	Threshold limits (%)
Methylene bis(phenyl isocyanate)	9016-87-9	>= 1 %
Methylene bis(phenyl isocyanate)	101-68-8	>= 1 %
Methylene bis(phenyl isocyanate)	5873-54-1	>= 1 %

Special Management Materials

Not applicable

Controlled Substances Subject to Environment Monitoring

Chemical name	CAS-No.	Threshold limits (%)
Methylene bis(phenyl isocyanate)	9016-87-9	>= 1 %
Methylene bis(phenyl isocyanate)	101-68-8	>= 1 %
Methylene bis(phenyl isocyanate)	5873-54-1	>= 1 %

Controlled Substances Subject to Health Examination

SAFETY DATA SHEET

SikaForce®-050 (B)



Version
3.0

Revision Date:
27.03.2024

SDS Number (Internal):
000000217609

Date of last issue: 28.03.2022
Date of first issue: 08.11.2019

Chemical name	CAS-No.	Threshold limits (%)
Methylene bis(phenyl isocyanate)	9016-87-9	>= 1 %
Methylene bis(phenyl isocyanate)	101-68-8	>= 1 %
Methylene bis(phenyl isocyanate)	5873-54-1	>= 1 %

Regulation under the Chemicals Control Act

Toxic Chemicals

Not applicable

Restricted Chemicals

Not applicable

Prohibited Chemicals

Not applicable

Toxic Release Inventory

Chemical name	CAS-No.	Group	Threshold limits (%)
Diphenylmethane 4,4'-diisocyanate	101-68-8	Group II	>= 1 %

Accident Precaution Chemicals

Not applicable

Dangerous Substances Safety Management Act

Classification : Group 4, Flammable liquids, Type 4 petroleums

Hazard rank : Hazardous rank III

Designated Quantity : 6000 litre

Safety Warning : Keep away from fire

International Chemical Weapons Convention (CWC) : Not applicable
Schedules of Toxic Chemicals and Precursors

라. Wastes Control Act

Industrial general wastes
Follow article 13 of the act to dispose the product waste

마. Other requirements in domestic and other countries

The components of this product are reported in the following inventories:

ENCS : On the inventory, or in compliance with the inventory

ISHL : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

16. OTHER INFORMATION

SAFETY DATA SHEET

SikaForce®-050 (B)



Version
3.0

Revision Date:
27.03.2024

SDS Number (Internal):
000000217609


Date of last issue: 28.03.2022
Date of first issue: 08.11.2019

Issuing date : 08.11.2019

Revision number and date

Number of Revision : 3.0
Revision Date : 27.03.2024
Date format : yyyy/mm/dd

NFPA:



Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
KR OEL : Harmful Agents to be kept below Occupational Exposure Limits
KR PEL : Harmful Agents Required to be kept below Permission Levels
ACGIH / TWA : 8-hour, time-weighted average
KR OEL / TWA : Time Weighted Average
KR PEL / TWA : TWA
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS : Chemical Abstracts Service
DNEL : Derived no-effect level
EC50 : Half maximal effective concentration
GHS : Globally Harmonized System
IATA : International Air Transport Association
IMDG : International Maritime Code for Dangerous Goods
LD50 : Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50 : Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL : International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL : Occupational Exposure Limit
PBT : Persistent, bioaccumulative and toxic

SAFETY DATA SHEET

SikaForce®-050 (B)



Version
3.0

Revision Date:
27.03.2024

SDS Number (Internal):
000000217609

Date of last issue: 28.03.2022
Date of first issue: 08.11.2019

PNEC : Predicted no effect concentration
REACH : Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC : Substances of Very High Concern
vPvB : Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.
KR / EN